

Appendix A
Compilation of TOTCO Borehole Deviation Surveys
Camp Stanley Storage Activity
TO42

DEPTH (feet bgs)	WELL IDENTIFICATION													
	MW1-BS	MW1-CC	MW2-CC	MW11A-LGR	MW11B-LGR	MW12-LGR	MW12-BS	MW12-CC	MW16-CC	MW17-LGR	MW18-LGR	MW19-LGR	MWH-LGR	
50'	1/16°	1/2°	1/2°	1/4°	1/16°	0°	1/4°	0°	1/2°	1/8°	1°	1/2°	1/2°	
100'	1/4°	1/4°	3/4°	1/16°	1/16°	0°	1/4°	1/2°	1/2°	0°	1°	1/2°	3/8°	
150'	1°	1/4°	3/4°	1/2°	1/2°	3/8°	1/4°	1/2°	3/4°	0°	1 1/4°	7/8°	1/4°	
200'	1 1/2°	1/8°	1 1/4°	1/4°	3/4°	1/2°	1/4°	1/4°	1°	1/8°	1°	3/4°	1/4°	
250'	1 1/4°	1/2°	1 1/2°	1/2°	1/2°	1°	1/4°	3/4°	1°	0°	1°	7/8°	1/2°	
300'	1°	1/8°	1 3/4°	3/4°	TD = 260'	1°	1/16°	1/2°	1°	1/2°	1°	3/4°	1/16°	
350'	1/2°	1/8°	1 3/4°	1°		7/8°	1/16°	1/4°	1°	3/4°	1 1/2°	7/8°	1/16°	
400'	TD = 366'	1/4°	1 1/4°	1°		TD = 358.5'	1/4°	1/2°	1°	3/4°	13/4°	TD = 365'	1/16°	
450'		TD = 420'	1 1/2°	TD = 445.5'			TD = 408'	3/4°	TD = 431'	TD = 392'	TD = 411'		TD = 382'	
500'			TD = 451'				TD = 465.5'							

Notes:

All measurements were collected using an MD Totco declination tool, double-punched on a 7° target.